

Amendment and Response

Applicant: Raymond H. Kraft

Serial No.: 10/800,420

Filed: March 12, 2004

Docket No.: A126.253.102

Title: SYSTEM AND METHOD OF NON-LINEAR GRID FITTING AND COORDINATE SYSTEM MAPPING

IN THE CLAIMS

Please add claim 40.

Please amend claims 1, 2, 16, 29, and 37 as follows:

1. (Currently Amended) A method of fitting acquired fiducial data to a set of fiducials on a fiducial plate; said method comprising:

translating an imaging apparatus across a plane parallel to the fiducial plate to capture image data such that image features of the image data is captured at discrete locations and positioned in space relative to the fiducial plate;

fitting a fiducial grid model to the image data acquired by ~~an~~ the imaging apparatus for each discrete location to identify image feature center~~captured such that features are positioned in space relative to the fiducial plate;~~

establishing a conversion from ~~acquired~~ coordinates obtained from the image data to ideal fiducial coordinates using a data processing component based on fitting the fiducial grid model for each discrete location;

calculating an absolute location for each identified acquired image feature centers relative to the fiducial plate in fiducial plate coordinates based on the conversion using the data processing component, the absolute location indicating a distance measurement in fiducial plate coordinates; and

based on at least one calculated absolute location of the identified acquired image feature centers, selectively modifying a structure represented by the identified acquired image feature center.

2. (Currently Amended) The method of claim 1 wherein said fitting comprises identifying fiducial coordinates for each fiducial captured in said image data acquired by said imaging apparatus.

Amendment and Response

Applicant: Raymond H. Kraft

Serial-No.: 10/800,420

Filed: March 12, 2004

Docket No.: A126.253.102

Title: SYSTEM AND METHOD OF NON-LINEAR GRID FITTING AND COORDINATE SYSTEM MAPPING

3. (Original) The method of claim 2 further comprising selectively iterating said identifying coordinates for each fiducial and said calculating an absolute location of identified acquired image feature centers.

4. (Original) The method of claim 1 wherein said calculating comprises utilizing a linear least squares operation.

5. (Original) The method of claim 1 further comprising assuming that a rotation of said imaging apparatus relative to a fiducial grid is negligible.

6. (Original) The method of claim 1 wherein said imaging apparatus comprises a charge-coupled device camera.

7. (Original) The method of claim 1 wherein said imaging apparatus comprises a complementary metal-oxide semiconductor device.

8. – 15. (Cancelled)

16. (Currently Amended) A computer readable medium encoded with non-transitory data and instructions for fitting acquired fiducial data to a set of fiducials on a fiducial plate; said data and said instructions causing an apparatus executing said instructions to:

translate an imaging apparatus across a plane parallel to the fiducial plate to capture image data such that image features of the image data is captured at discrete locations and positioned in space relative to the fiducial plate;

fit a fiducial grid model to the image data acquired by an the imaging apparatus for each discrete location to identify image feature center~~captured such that features are positioned in space relative to the fiducial plate;~~

Amendment and Response

Applicant: Raymond H. Kraft

Serial No.: 10/800,420

Filed: March 12, 2004

Docket No.: A126.253.102

Title: SYSTEM AND METHOD OF NON-LINEAR GRID FITTING AND COORDINATE SYSTEM MAPPING

establish a conversion from ~~acquired~~ coordinates obtained from the image data of each identified fiducial to ideal plate coordinates based on fitting the fiducial grid model for each discrete location; and

calculate an absolute location of each identified acquired image feature centers relative to the fiducial plate, the absolute location indicating a distance measurement in fiducial plate coordinates.

17. (Original) The computer readable medium of claim 16 further encoded with data and instructions; said data and said instructions further causing an apparatus executing said instructions to identify fiducial coordinates for each fiducial captured in said data acquired by said imaging apparatus.

18. (Original) The computer readable medium of claim 17 further encoded with data and instructions; said data and said instructions further causing an apparatus executing said instructions selectively to iterate identifying coordinates for each fiducial and calculating an absolute location of identified acquired image feature centers.

19. (Original) The computer readable medium of claim 16 further encoded with data and instructions; said data and said instructions further causing an apparatus executing said instructions to utilize a linear least squares operation.

20. (Original) The computer readable medium of claim 16 further encoded with data and instructions; said data and said instructions further causing an apparatus executing said instructions to assume that a rotation of said imaging apparatus relative to a fiducial grid is negligible.

21. – 28. (Cancelled)

Amendment and Response

Applicant: Raymond H. Kraft

Serial No.: 10/800,420

Filed: March 12, 2004

Docket No.: A126.253.102

Title: SYSTEM AND METHOD OF NON-LINEAR GRID FITTING AND COORDINATE SYSTEM MAPPING

29. (Currently Amended) A method of accurately identifying a location of a feature relative to a fiducial plate comprising:

- acquiring an image data of an object with an imaging apparatus by translating the imaging apparatus across a plane parallel to a fiducial plate to capture the image data at discrete locations, the image ~~comprising~~ data concerning the position of a plurality of fiducial marks on a fiducial plate and data concerning the position of a feature of the object, the image data being acquired such that the image data concerning the position of a plurality of fiducial marks on a fiducial plate and data concerning the position of a feature of the object is obtained simultaneously;
- fitting a fiducial grid model to the image data to establish a conversion from coordinates of the plurality of fiducial marks acquired from the image to coordinates of the plurality of fiducial marks on the fiducial plate using a data processing component;
- calculating an absolute location of a center of each of the plurality of fiducial marks in the acquired image relative to the fiducial plate in fiducial plate coordinates using the data processing component, the absolute location indicating a distance measurement in fiducial plate coordinates; and,
- determining a position of a feature of the object in the acquired image and modifying the determined position based on at least one calculated absolute location of the plurality of fiducial marks in the acquired image.

30. (Previously Presented) The method of claim 29 wherein the fitting comprises identifying fiducial mark coordinates for each fiducial mark captured in the image data acquired by the imaging apparatus.

31. (Previously Presented) The method of claim 30 further comprising selectively iterating the identifying coordinates for each fiducial mark and the calculating an absolute location of identified acquired image feature centers.

Amendment and Response

Applicant: Raymond H. Kraft

Serial No.: 10/800,420

Filed: March 12, 2004

Docket No.: A126.253.102

Title: SYSTEM AND METHOD OF NON-LINEAR GRID FITTING AND COORDINATE SYSTEM MAPPING

32. (Previously Presented) The method of claim 29 wherein the calculating comprises utilizing a linear least squares operation.

33. (Previously Presented) The method of claim 29 further comprising assuming that a rotation of the imaging apparatus relative to the fiducial plate is negligible.

34. (Previously Presented) The method of claim 29 wherein the imaging apparatus comprises a charge coupled device camera.

35. (Previously Presented) The method of claim 29 wherein the imaging apparatus comprises a complementary metal-oxide semiconductor device.

36. (Previously Presented) The method of claim 29 wherein the object is part of a semiconductor probe card.

37. (Currently Amended) A method of localizing an object, comprising:

acquiring an image data with an imaging apparatus by translating the imaging apparatus across a plane parallel to a fiducial plate to capture the image data such that image features of the image data is captured at discrete locations and positioned in space relative to the fiducial plate, wherein the discrete locations are less than or equal to half of a center-to-center fiducial spacing as measured on the fiducial plate, the image data including the object to be localized and a plurality of fiducial marks;
fitting a model to the plurality of fiducial marks that defines a transformation between a location of the plurality of fiducial marks as seen in the image data acquired during the translating of the imaging apparatus and an actual location of the plurality of fiducial marks;

Amendment and Response

Applicant: Raymond H. Kraft

Serial No.: 10/800,420

Filed: March 12, 2004

Docket No.: A126.253.102

Title: SYSTEM AND METHOD OF NON-LINEAR GRID FITTING AND COORDINATE SYSTEM MAPPING

determining an actual position of the object with respect to the plurality of fiducial marks
using the model fitted to the image of the plurality of fiducial marks as the
imaging apparatus is translated.

38. (Previously Presented) The method of claim 37 further comprising:

interposing a substantially transparent substrate having a plurality of fiducials formed
therein between the imaging apparatus and the object.

39. (Previously Presented) The method of claim 37 further comprising:

acquiring a succession of images with an imaging apparatus, each of the succession of
images including both the object and the plurality of fiducial marks.

40. (New) The method of claim 1, wherein the image data includes object data and fiducial data.